

PG-DS4S-1FR ONE HOUR FIRE RATED BUNDED IBC/DRUM STORE

PRODUCT OVERVIEW

Whether you are looking for oil storage, chemical storage, drum storage or IBC storage our secure bunded storage units are fully compliant with current UK regulations. Our extensive range of bunded storage units provide an immediate solution to the problems encountered with environmental, health and safety legislations.

Petrogear can manufacture custom size units for the type and amount of containers you wish to store.



STANDARD FEATURES

- 60 Minute fire protection to BSEN 746:PART 22 and BSEN 1634-1:2000
- Entire sump base & structural frame is constructed from 6mm SHS & plate
- Forklift pockets through the entire base
- Double wall construction – all exterior walls, roof and door are made from 3mm fully welded corrugated sheets, 50mm internal air gap insulated with 60 Min. Rockwool Fire Batt Insulation, and the interior is lined with 2mm Zintec panels.
- Fully welded sloped roof with crane lifting points – 2000Kg M.G.W.
- Heavy duty hinges and lockable container lock bar assembly
- Fully ventilated high/low with PYROPLEX® Intumescent fire rated Air Vents
- Fire door fully sealed with PYROPLEX® Intumescent fire rated door strips
- Fully seam welded bund is leak tested & exceeds EPA requirements
- The base floor and upper shelf are made with galvanized steel grating enabling spilled chemicals to pass into the bunded sump.
- Unit is sprayed with zinc-rich epoxy primer, top coat & clear coat
- Safety warning signage



SPECIFICATIONS

Exterior Dimensions	1600mm (L) x 1600mm (W) x 2700mm (H)		
Bunded Sump Capacity	488Ltr.	Tare Weight Kg.	1450 Kg
Color	Green RAL 6029 or special request		
Number of Containers	Four 205Ltr Drums, One IBC, upper shelf for 25Ltr. cans		