

PG-3" ROTARY SWIVEL

PRODUCT OVERVIEW

Petrogear swivels are designed and machined to be durable and easy to maintain onsite and we can custom machine the bottom and side connections to your requirements.

STANDARD FEATURES

- All parts are integral
- AISI Grade 4140 material
- Thread Specification certified to API 7-1
- Magnesium Phosphating done on both connections
- Swivel supplied with pressure test reports
- Swivel supplied with parts list diagram
- Swivel supplied with maintenance assembly manual
- Swivel supplied with full material traceability certificates
- Supplied with a custom made storage case to house the swivel and spares
- Bottom and side thread protection caps
- Lifting padeye is machined from the solid upper block eliminating the requirement for regular load testing and MPI inspections
- Maintenance tools supplied



SPECIFICATIONS

Exterior Dimensions	1100mm (L) x Ø 350mm	Max. Pressure Static	15000 PSI
Side Outlet Connection	3" FIG 1502 H2S Male	Tare Weight	900 Kg
Max. Speed RPM	250 rpm	Course Bore Ø	3" (76.2mm)
Finish	Electroplated, Nickle hard chrome finish at seal locations, epoxy painted		
Typical Bottom connection (box & pin)	4" NC 40 VAM EIS Box	Or special request	